


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>C08K 5/3435, 5/20, C08L 23/02</b>		A1	(11) International Publication Number: <b>WO 97/39052</b> (43) International Publication Date: <b>23 October 1997 (23.10.97)</b>
<b>(21) International Application Number:</b> PCT/US97/05679 <b>(22) International Filing Date:</b> 4 April 1997 (04.04.97)		<b>(81) Designated States:</b> KR, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
<b>(30) Priority Data:</b> 60/015,649 12 April 1996 (12.04.96) US		<b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
<b>(71) Applicant (for all designated States except US):</b> CLARIANT FINANCE (BVI) LIMITED [--]; Citco Building, Wickhams Cay, Road Town, Tortola (VG). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> WEBSTER, Joseph, R. [US/US]; 10705 Summit Tree Court, Charlotte, NC 28277 (US). <b>(74) Agent:</b> McCANN, Philip, P.; Clariant Corporation, 4000 Monroe Road, Charlotte, NC 28205 (US).			

(54) Title: STABILIZATION OF POLYOLEFINS



## (57) Abstract

The subject matter of the invention is the use of certain piperidine compounds of formula (I) in combination with an oxalanide UV absorber for the stabilization of pigmented or unpigmented polyolefins against the negative consequences of UV radiation. The invention also relates to compositions comprising a piperidine compound of formula (I), a polyolefin, and an oxalanide UV absorber and compositions comprising a compound of formula (I) and a second HALS compound.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		

**Stabilization of Polyolefins**

The subject matter of the invention is the use of certain piperidine compounds of formula I in combination with an oxalanide UV absorber for the stabilization of 5 pigmented or unpigmented polyolefins against the negative consequences of light, in particular UV radiation (290-420 nm). The invention also relates to a composition comprising a piperidine compound of formula I, a pigmented or unpigmented polyolefin, and an oxalanide UV absorber. A further object of the invention is a process for the stabilization of pigmented or unpigmented polyolefins 10 against the negative consequences of light which comprises adding to said polyolefins a quantity sufficient for stabilization of at least one piperidine compound of formula I and an oxalanide UV absorber.

Polyolefins, either pigmented or unpigmented, can be damaged by energy 15 introduced in the form of light. Pigments are insoluble or extremely poorly-soluble dyestuffs which contain groups of atoms normally referred to as chromophoric groups, which create the color quality of molecules, and auxochromic groups, which themselves do not create any color but strengthen the intensity and depth of color. The invention also concerns the color fastness of pigments. For example, in a 20 colored, ready-made article, which during the course of its use is subjected to the influence of natural or artificial light, especially the UV part thereof, the established shade is altered, or its intensity, i.e. depth of color, is reduced.

It is therefore an aim of the invention to improve the light fastness and color 25 intensity of pigmented polyolefins and the usage period of the pigmented finished articles.

It is known that compounds of the HALS type (HALS = hindered amine light 30 stabilizer) react as radical traps, and are therefore used for the stabilization of polymeric substrates. However, these commercial HALS compounds do not have


specific, light-stabilizing activity on pigments. It has surprisingly been found that the presence of piperidine compounds of formula I in combination with UV absorbers, especially oxalanide UV absorbers, substantially improves the stability of polyolefins against the adverse effects of light.

5

The subject matter of the invention is thus a composition comprising:

- a) a polyolefin;
- b) a piperidine compound of formula I

10



wherein

$R_1$  is hydrogen, hydroxyl, low molecular weight alkyl, low molecular weight alkoxy, or acyl;

$R_2$  is a mono- or binuclear aromatic group which optionally bears substituents;

15  $R_3$  is oxygen,  $-NH-$  or  $-N(C_{1-4}\text{-alkyl})-$ ; and

each  $R_8$ , independently of one another, is hydrogen or methyl; and  
c) an oxalanide UV absorber.

All the  $R_8$ 's preferably are hydrogen.

20

Another embodiment of the invention is a composition as described above wherein

a) is polypropylene, polyethylene, or a copolymer thereof;

$R_1$  is hydrogen,  $C_{1-8}\text{-alkyl}$ ,  $C_{1-8}\text{-alkoxy}$ , formyl, acetyl, or propionyl;

$R_2$  is benzene, naphthalene, or a nitrogen and/or sulphur containing five- or six-


membered ring, which is optionally anellated to a benzene ring;  
 R<sub>3</sub> is oxygen, -NH-, or -N-(C<sub>1-4</sub>-alkyl);  
 R<sub>8</sub> is hydrogen; and  
 c) is 2-ethyl-2'-ethoxy-oxalanilide or N-(2-ethoxyphenyl)-N'-(4-isododecylphenyl)-  
 5 ethanediamide.

Another embodiment of the invention is a composition comprising b) and c), as defined above, in the range of ratios (wt/wt.) of 4:1 to 1:4, especially 3:1, 2:1, 1:1, 1:2, and 1:3. These compositions may also comprise one or more additional HALS 10 compounds, UV absorbers, primary and secondary antioxidants, and antacids (i.e., acid acceptors).

Another embodiment of the invention is a composition comprising a piperidine compound of formula I and a second HALS compound in the range of ratios (wt./wt.) of 3:1 to 1:3, especially 2:1, 1:1, and 1:2. Said second HALS include 15 commercially available products such as Tinuvin 123 and 622, Chimassorb 944 and 119, HA88, and Uvisil 299 and 2000.

The following compounds of formula Ia are preferred

20



wherein

25 R<sub>1</sub> is H, CH<sub>3</sub>, OC<sub>6</sub>H<sub>17</sub>, C(O)CH<sub>3</sub>, or p-C<sub>1-8</sub>alkoxy-substituted benzene; and  
 R<sub>4</sub> is H or OCH<sub>3</sub>

Most preferred is a compound of formula Ia wherein R<sub>1</sub> is CH<sub>3</sub> and R<sub>4</sub> is OCH<sub>3</sub>.

The compounds of formula I may be prepared by methods taught in GB 2,269,819,

5 published February 23, 1994 and DE 3,412,227, published October 11, 1984.


The polyolefins are preferably polypropylene, polyethylene, and copolymers thereof. The polypropylene is preferably polypropylene fiber and thick section polypropylene.

10 Polypropylene fiber means the unit that forms the basic element of fabrics and other textile structures and is characterized by having a length at least 50 times its diameter or width. The term, as used herein, includes fibers, yarns, slit tapes, and fabrics. Thick section polypropylene means a polypropylene article having a thickness or diameter of at least 20 mils or from 600 to greater than 1000 microns.

15 "Low molecular weight alkyl" means groups with 1 to 8, especially 1 or 2, carbon atoms,

"Acyl" means the radicals of formic, acetic, or propionic acid.

20 The mono- or binuclear aromatic group R<sub>2</sub> are, e.g., benzene, naphthalene, and nitrogen and/or sulphur containing five- or six-membered rings, which are optionally anellated to a benzene ring, and which bear, e.g., a sterically hindered hydroxyl as a substituent (3,5-ditert.-butyl-4-hydroxyphenyl), or a thienyl group. Aromatic six-membered rings are preferred. The substituents which may be present on these 25 rings are, e.g., hydroxyl, low molecular weight alkyl or alkoxy, preferably methyl, tert.-butyl, methoxy, ethoxy, hydroxyl, and one or two groups of formula



In addition to the piperidine compounds of formula I and the oxalanide UV absorber, further commercial additives may be additionally employed in the 5 polyolefin substrates, such as primary or secondary anti-oxidants or mixtures thereof, secondary aromatic amines, thioethers, phosphorus compounds, biocides, metal deactivators, further HALS compounds, further UV absorbers, anti-static agents, and the like, as well as various finishing assistants or inert filler materials, e.g. talcum, mica,  $\text{TiO}_2$ , chalk, glass, barite, acid acceptors (antacids) etc.

10

The metal deactivators include commercially available compounds such as Irganox 1024 and Naugard XL-1.

15 The UV absorbers include hydroxy-substituted benzophenones such as Cyasorb UV 9, 24, 207, 284, 416, 531, and 2126; Uvinul 3000, 3008, 3040, 3049, 3050, and 3060; hydroxy-substituted benzotriazoles such as Cyasorb 5411 and Tinuvin 234, 326, 327, 328, 384, 900, and 1130; triazines such as Cyasorb 1164 and 1164(L), Tinuvin 1577, and Uvinul T-150; salicylic acid ester; formamidine; cyanoacrylates such as Uvinul 3038 and 3039; and benzylidenmalonate esters such as Cyasorb 20 1988.

The acid acceptors include metallic oxides and stearates and  $\text{MgAlOH}$  carbonates.

Finished articles stabilized according to the invention are superior to articles according to the prior art in respect of their substantially longer period of use.

5      The compound of formula I (b) and the UV absorber (c) or a composition comprising (b) and (c) may be added to the pigmented or unpigmented polyolefin substrate before, during or, after the manufacture thereof. Pigments are intended to include all organic and inorganic (e.g., Ultramarine Blue,  $TiO_2$ ) pigments.

10     The concentration of the piperidine compound of formula I is 0.01 to 2% by weight, preferably 0.1 to 1%, based on polyolefin a). The concentration of UV absorber c) is 0.01 to 1% by weight, preferably 0.05 to 1%, most preferably 0.1 to 0.6%, based on polyolefin a). The concentration of a composition comprising a piperidine compound of formula I and a second HALS compound in the range of ratios of 3:1 to 1:3 is 0.01 to 1% by weight, based on polyolefin a). The addition of the 15     pigmentation to polyolefin may be effected in accordance with generally conventional processes in pure form as so-called full pigments, in pre-dispersed form as concentrates, masterbatches and the like, or in combination with further admixtures.

20     A further object of the invention is a process for the stabilization of pigmented or unpigmented polyolefins against the negative consequences of light which comprises adding to said polyolefins a quantity sufficient for stabilization of at least one piperidine compound of formula I and an oxalanide UV absorber c).

25     In the following examples which illustrate the invention, the parts and percentages are by weight, and the degrees are degrees celsius.

EXAMPLE 1UV Stability

5 To test the stability of polypropylene treated with the composition of the invention against the adverse effects of UV radiation, tests were conducted on 600/34 natural 10 yarns (18 dpf) treated as follows:

A melt compounded masterbatch of 10% (wt.) HALS (either one or a combination of HALS) was prepared and let down into a 8 MF (melt flow in g/10 minutes) 15 polypropylene homopolymer and melt compounded (i.e., extrusion compounded) at 216-221°C into pelletized form. The pelletized resin contained either HALS alone or in combination with UVA. An appropriate amount of pelletized resin was melt extruded into 18 dpf fibers at 265°C to yield the various concentrations of test materials and prepared into fabric.

15

The compounds used were:

HALS 1	is	Chimassorb 944, poly[[ $\beta$ -[1,1,3,3-tetramethyl butyl] amino]-s-triazine-2,4-diyl][[2,2,6,6-tetramethyl-4-piperidyl]imino]hexamethylene
20		[(2,2,6,6,-tetramethyl-4-piperidyl)imino]]
HALS 2	is	Chimassorb 119, 1,3,5-triazine-2,4,6-triamine, N,N''-[1,2-ethanediylbis[[[4,6-bis[butyl (1,2,2,6,6-pentamethyl-4-piperidinyl)amino]-1,3,5-triazine-2-yl]imino]-3,1 propanedyl]]-bis[N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-
25		
HALS 3	is	Tinuvin 123, bis-(1-octyloxy-2,2,6,6,tetra-30 methyl-4-piperidinyl)sebacate

Sanduvor® PR-31 is a compound of the formula Ia where R<sub>1</sub> is -OCH<sub>3</sub> and R<sub>4</sub> is methyl, propanedioic acid, [(4-methoxyphenyl)-methylene]-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)ester

5 UVA1 is Ferro AM 340, benzoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,4-bis(1,1-dimethylethyl)phenyl ester

10 UVA2 is Tinuvin 234, 2-(2H-benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol

Sanduvor® VSU is 2-ethyl-2'-ethoxy-oxalanilide

15 The tests were run using test standard SAE J 1885 at 89°C and a high temperature xenon lamp. Test results are in KJ/m<sup>2</sup> to degradation. The data demonstrate that PR-31 alone (test 3) or in combination with another HALS compound, especially an aminoether type HALS such as Tinuvin 123, enhances polypropylene stability against the degradation by UV light when compared to combinations of other HALS compounds (e.g., compare tests 5 and 6) and that PR-31 also enhances this 20 stability when used in combination with a UV absorber (e.g., compare tests 9 and 10), the best of which absorbers is Sanduvor® VSU (e.g., compare tests 12, 13, and 14).

25 ®Sanduvor is a registered trademark of Sandoz Ltd.

TABLE 1-1

		% Additive Used							
		1	2	3	4	5	6	7	8
5	HALS 1	0.6							
	HALS 2		0.6			0.3		0.3	
	HALS 3				0.6	0.3	0.3		
10	Sanduvor PR-31			0.6			0.3		0.3
	UVA 1							0.3	0.3
	UVA 2								
15	Sanduvor VSU								
	Results	902.4	1353.6	1466.4	1128	1240.8	1579.2	676.8	1466.4

TABLE 1-1 (cont.)

5

10

15

	% Additive Used							
	9	10	11	12	13	14	15	16
HALS 1								
HALS 2	0.3		0.3		0.3		0.6	
HALS 3								
Sanduvor PR-31		0.3		0.3		0.3		0.6
UVA 1								
UVA 2					0.3	0.3		
Sanduvor VSU			0.3	0.3			0.3	0.3
Results	564	1240.8	902.4	1804.8	564	1466.4	564	2594.4

**EXAMPLE 2**  
**Pigmented Fiber**

5 To test the stability of pigmented polypropylene with the compositions of the invention, an 8 dpf automotive fiber was prepared pigmented with 1.0% to TiO<sub>2</sub>. The tests were run using test standard Amoco Fabrics & Fibers Internal Scratch Test Method. Test results (HTX) are in hours to failure.

10

TABLE 2-1


15

Test	HALS 0.72%	UVA 0.36%	HTX
1	PR-31	VSU	3853
2	HALS2	UVA2	2594

20

**What is claimed is:**

1. A composition comprising:
- a) a polyolefin;
- 5 b) a piperidine compound of formula I



wherein


$\text{R}_1$  is hydrogen, hydroxyl, low molecular weight alkyl, low molecular weight alkoxy,  
10 or acyl;  
 $\text{R}_2$  is a mono- or binuclear aromatic radical which optionally bears substituents;  
 $\text{R}_3$  is oxygen,  $-\text{NH}-$ , or  $-\text{N}(\text{C}_{1-4}\text{-alkyl})-$ ; and  
each  $\text{R}_8$ , independently of one another, is hydrogen or methyl; and  
c) an oxalanide UV absorber.

15

2. A composition of claim 1, wherein
  - a) is polypropylene, polyethylene, or a copolymer thereof;
  - $\text{R}_1$  is hydrogen,  $\text{C}_{1-6}$ -alkyl,  $\text{C}_{1-6}$ -alkoxy, formyl, acetyl, or propionyl;
  - $\text{R}_2$  is benzene, naphthalene, or a nitrogen and/or sulphur containing five- or six-  
20 membered ring, which is optionally anellated to a benzene ring;
  - $\text{R}_3$  is oxygen,  $-\text{NH}-$ , or  $-\text{N}(\text{C}_{1-4}\text{-alkyl})-$ ;
  - $\text{R}_8$  is hydrogen; and
  - c) is 2-ethyl-2'-ethoxy-oxalanilide or  $\text{N}-(2\text{-ethoxyphenyl})\text{-N}'-(4\text{-isododecyphenyl})$ -ethanediamide.

3. A composition of claim 2, wherein the piperidine compound is formula Ia

5



wherein

- 10 a) is a polypropylene;
- R<sub>1</sub> = H, CH<sub>3</sub>, OC<sub>8</sub>H<sub>17</sub>, C(O)CH<sub>3</sub>, or p-C<sub>1-6</sub>-alkoxy-substituted benzene;
- R<sub>4</sub> = H or OCH<sub>3</sub>; and
- c) is 2-ethyl-2'-ethoxy-oxalanilide.

4. A composition of claim 3 wherein R<sub>1</sub> is CH<sub>3</sub> and R<sub>4</sub> is OCH<sub>3</sub>.

15

5. A compound of claim 1, wherein the concentration of piperidine compound b) is 0.01 to 2% by weight, preferably 0.1 to 1%, based on polyolefin a); and the quantity of UV absorber is 0.01 to 1% by weight, preferably 0.05 to 1%, more preferably 0.1 to 0.6%, based on polyolefin a).

20

6. A composition of claim 1, wherein the substrate is polypropylene fiber or thick section polypropylene.

25


7. A composition of claim 1, wherein the polyolefin contains admixtures selected from the group consisting of anti-oxidants, finishing assistants, further light-protection agents, fillers, strengthening agents, and adjuvant substances.

8. A composition of claim 1 wherein the polyolefin contains organic or inorganic pigments.

9. A composition prepared by a process which comprises mixing

5      a) a polyolefin;

      b) A piperidine compound of formula I



wherein

10       $\text{R}_1$  is hydrogen, hydroxyl, low molecular weight alkyl, low molecular weight alkoxy, or acyl;

$\text{R}_2$  is a mono- or binuclear aromatic radical which optionally bears substituents;

$\text{R}_3$  is oxygen,  $-\text{NH}-$ , or  $-\text{N}(\text{C}_{1-4}\text{-alkyl})-$ ; and

      each  $\text{R}_8$ , independently of one another, is hydrogen or methyl; and

15      c) an oxalanide UV absorber.

10. A process for stabilizing a pigmented or unpigmented polyolefin against the negative consequences of light which comprises adding thereto a quantity sufficient for stabilization of a composition comprising a piperidine compound of formula I and

20      an oxalanide UV absorber.

11. A process of claim 10, wherein

      a) is polypropylene, polyethylene, or a copolymer thereof;

$\text{R}_1$  is hydrogen,  $\text{C}_{1-6}$ -alkyl,  $\text{C}_{1-6}$ -alkoxy, formyl, acetyl, or propionyl;

$R_2$  is benzene, naphthalene, or a nitrogen and/or sulphur containing five- or six-membered ring, which is optionally anellated to a benzene ring;

$R_3$  is oxygen, -NH-, or -N-( $C_{1-4}$ -alkyl); and

$R_6$  is hydrogen.

**INTERNATIONAL SEARCH REPORT**

International Application No  
PCT/US 97/05679

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 C08K5/3435 C08K5/20 C08L23/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 C08K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	RESEARCH DISCLOSURE, vol. 389, no. 10, September 1996, EMSWORTH, GB, pages 541-545, XP000635466 "polymer stabilizers" see page 542, column 1, paragraph 5 ---	1-4
P,A P,X	WO 97 07159 A (CLARIANT) 27 February 1997 see page 3, paragraph 3 see claims 1,4; examples DA-DC ---	1,4,5 1,5
P,X	GB 2 301 823 A (CLARIANT) 18 December 1996 see claims 1,2,7 see page 1, paragraph 3 - page 3, paragraph 3 ---	1,4,5
		-/-

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

1	Date of the actual completion of the international search  13 August 1997	Date of mailing of the international search report  03.09.97
	Name and mailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax (+ 31-70) 340-3016	Authorized officer  Engel, S

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 97/05679

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	LIGNER ET AL.: "Addcon 96, paper 7: "how to increase HALS persistence in polyolefins ---" 1996, RAPRA TECHNOLOGY, SHREWSBURY, UK XP002037628 see page 1 - page 8 ---	1-4
A	DE 34 12 227 A (SANDOZ) 11 October 1984 cited in the application see page 7, paragraph 3; claims 1,4,5 ---	1-3
A	EP 0 389 427 A (CIBA) 26 September 1990 see page 9, line 36 - line 40; claims 1,28; example 22 -----	1,4

1

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International Application No

PCT/US 97/05679

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9707159 A	27-02-97	DE 19530468 A AU 6822296 A JP 9059459 A	20-02-97 12-03-97 04-03-97
GB 2301823 A	18-12-96	DE 19622710 A FR 2735139 A JP 8337682 A	12-12-96 13-12-96 24-12-96
DE 3412227 A	11-10-84	NONE	
EP 389427 A	26-09-90	CA 2012503 A DE 69008405 D DE 69008405 T JP 2300168 A US 5021478 A	21-09-90 01-06-94 25-08-94 12-12-90 04-06-91